

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau(43) International Publication Date
18 November 2004 (18.11.2004)

PCT

(10) International Publication Number
WO 2004/099586 A1(51) International Patent Classification⁷: F02B 37/22,
37/013(21) International Application Number:
PCT/IB2003/001787

(22) International Filing Date: 8 May 2003 (08.05.2003)

(25) Filing Language: English

(26) Publication Language: English


(71) Applicant (for all designated States except US): HONEY-
WELL INTERNATIONAL INC. [US/US]; 101 Colum-
bia Road, Morristown, NJ 07962-1057 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): KUMABE, Sergio,
Tetsuo [BR/BR]; Rua Francisco Martins Feitosa, 790,
Mogi das Cruzes, Sao Paulo, CEP 08735-420 (BR).(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.(54) Title: CONTROL VALVE AND PARTS OF A TURBOCHARGER AND A TURBOCHARGER BOOSTING SYSTEM COM-
PRISING THE SAME(57) Abstract: A control valve comprises a movable
flap (15) for a controlled closing or opening of a fluid
passage (9, 3), wherein in the closed state the upstream
side of said flap (15) extends in a plane being inclined
to the extension direction of the passage (9, 3). Such a
control valve is used in a turbine housing or compressor
housing of a turbocharger.

WO 2004/099586 A1